


Casement Window

Alitherm 400i (Internally beaded)



Range	Smarts Alitherm 400i
Finish	Polyester powder coating to BS6496 (Marine Grade +60 microns)
Appearance	Square frame, with quick glaze bead and flat sash.
Stock colours	White gloss, RAL 7016m, RAL 9005m and Ral 7016m on white
System glazing	Internally glazed with dummy sashes in fixed lights + tap in bead
Thermal break	Polyamide thermally broken profile
Gaskets	Low line gasket for slimmer sightlines
WER	down to A+ rating using suitable double glazed unit
U Value	down to 1.4 W/m ² k with double glazing and 1.1 W/m ² k with 40mm triple glazing
Locking system	PAS24 approved mushroom espag locking mechanism by Smart/Yale
Security	PAS24 upgraded available (6.8mm lam glass/ hinge guards)
Hinges	Friction hinges by Yale
Handles on sash	Espag locking handles by ERA in the sash
Frame Depth	70mm
Typical sightline	81.5mm sash and outer frame
Side Hung Max o/a width	864mm
Side Hung Max o/a height	1400mm
Top Hung Max o/a width	1400mm
Top Hung Max o/a height	1500mm
Glazing sizes	28mm double glazed unit and 40mm triple glazed unit
Air Test	Class 4
Water test	E1200
Wind test	AE2400
Add ons	20mm and 42mm add on available
Cill sizes	85mm, 150mm, 190mm and 225mm
Service	
Quotes	within 24 hrs
Orders	2-3 weeks
Delivery	on dedicated Atlas vehicles