



ATLAS HERITAGE 60 RESIDENTIAL/FRENCH DOORS

Residential/French Doors

Heritage 60



Range	Smarts Heritage 60 door
Finish	Polyester powder coating to BS6496 (Marine Grade +60 microns)
Appearance	Contemporary frame and beads. Transoms required as above to support handle fixing
Stock colours	White gloss, RAL 7016m, RAL 9005m and Ral 7016m on white
System glazing	Internally glazed
Thermal break	Polyamide thermally broken profile
Gaskets	Low line gasket for slimmer sightlines
DER	down to B rating on french doors using suitable 28mm double glazed unit
U Value	down to 1.5 W/m2k with double glazing
Locking system	2no hook bolts and a dead bolt by Smart
Security	PAS24 upgraded specification available
Cylinder	UAP 3 star cylinder
Hinges	Barrell hinges by Smart
Handles	Key locking handles by ERA
Frame Depth	60mm
Typical sightline	67mm
Max o/a height per sash	2100mm
Max o/a width per sash	900mm
Max Sash weight	60kg
Glazing sizes	28mm double glazed unit
Air Test (single door)	Class 4 600Pa
Water test (single door)	Class 3A 100Pa
Wind test (single door)	Class 3 1200Pa
Add ons	20mm and 42mm add on available
Cill sizes	85mm, 150mm, 190mm and 225mm
Threshold	Low level threshold options available (down to 15mm)
Astragal bar	25mm flat astragal bar

Service	
Delivery	on dedicated Atlas vehicles