



ALITHERM 400 WINDOW ORDER/QUOTE FORM

☐ Please tick for quote only Page ____ of ____

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@atlas-aluminium.co.uk

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

(Please tick): Alitherm 400 Hybrid [] -Contemporary frame -flat sash -**INTERNALLY GLAZED SASH / EXTERNALLY GLAZED FIXED FRAMES** -square bead
 Alitherm 400i [] -Contemporary frame -flat sash - **INTERNALLY GLAZED** -square bead with dummy sashes
 Alitherm 400x [] -Contemporary frame -flat sash - **EXTERNALLY GLAZED** -square bead

Note: The Alitherm 400i and Hybrid glazed window systems are a 28mm tap in quickglaze bead as standard.

Note: Alitherm 400x windows and internally beaded Alitherm 400i triple glazed windows are wedge gasketed as standard.

Please Circle Items Required

Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q

Part Q Compliant: Y / N 400x/Hybrid Glass locks^(Q): Y / N

Colour: White (G) / Grey (7016M) / Black (9005M) /
 Dual Grey Ex (M) & White Int (G)

Handle Colour: White / Gold / Chrome / Black / Grey
 Satin Silver / Antique Black (Monkey tail)

Stayguards^(Q): Y / N

Trickle Vent Colour: White / Black / Grey / Silver / Grey on white
 Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm

Deep Head outer frame for trickle vent: Y / N

Drainage: Face / Concealed

Glass Supply: YES / Unglazed

Glass specification width^(Q): 28mm DGU 28.8mm lam DGU

Triple glazing- Alitherm 400i only: 40mm TGU 40.8mm lam TGU

If unglazed please tick above glass thickness for gasket type.

For externally glazed triple glazing use our REAL System 2 windows

Standard Thermal Rating:

Window Energy Rating A externally glazed and B internally glazed with 28mm Clear, 1.2 Softcoat, Argon, Black W/edge (Q)

Product U value Special Requirements: _____

Astragal bars for 28mm units only - please tick: [] 25mm Flat bar

Hinge codes:
 S=Standard / E=Egress easy / R=Restrictor / RE=Restrictor Egress (TRI R90)

T/V Trickle vents require a 30 or 42mm add-on, fixed to the top of the window

Location	Design (viewed outside, please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add ons 20mm 30mm 42mm (Deep head, 30 or 42mm required with t/vents)			Special Requirements
						T/V					
			W		None	S E		T			
					85	R RE		B			
			H		150	2700		L			
					190 / 225	4000		R			
			W		None	S E		T			
					85	R RE		B			
			H		150	2700		L			
					190 / 225	4000		R			
			W		None	S E		T			
					85	R RE		B			
			H		150	2700		L			
					190 / 225	4000		R			

Location	Design (viewed outside , please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add ons			Special Requirements
						T/V		20mm	30mm	42mm	
			W		None	S E		T			
					85	R RE		B			
			H		150	2700		L			
					190 / 225	4000		R			
			W		None	S E	T				
					85	R RE	B				
			H		150	2700	L				
					190 / 225	4000	R				
			W		None	S E	T				
					85	R RE	B				
			H		150	2700	L				
					190 / 225	4000	R				
			W		None	S E	T				
					85	R RE	B				
			H		150	2700	L				
					190 / 225	4000	R				
			W		None	S E	T				
					85	R RE	B				
			H		150	2700	L				
					190 / 225	4000	R				
			W		None	S E	T				
					85	R RE	B				
			H		150	2700	L				
					190 / 225	4000	R				
			W		None	S E	T				
					85	R RE	B				
			H		150	2700	L				
					190 / 225	4000	R				
			W		None	S E	T				
					85	R RE	B				
			H		150	2700	L				
					190 / 225	4000	R				