

**ALITHERM 400 TBT WINDOW ORDER/QUOTE FORM**Please tick for quote
only

Page ____ of ____

Aluminium Direct Fax: 01453 827801

E-mail Orders: sop@atlas-aluminium.co.uk

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

(Please tick):Alitherm 400i TBT [] -Contemporary frame - featured sash - **INTERNALLY GLAZED** - square bead**Please Circle Items Required****Please Circle Items Required**

(Q) = Selection may need to be upgraded to meet Part Q

Part Q Compliant: Y / N**Colour:** White (G) / Grey (7016M) / Black (9005M) /
Dual Grey Ex (M) & White Int (G)**Handle Colour:** White / Gold / Chrome / Black / Grey / Satin Silver**PAS24:** Y / N**Trickle Vent Colour:** White / Black / Grey / Silver / Grey on white
Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm**Drainage:** Face / Concealed**Glass Supply:** YES / Unglazed**Glass specification width^(Q):** 28mm DGU 28.8mm lam DGU^(Q)**Triple glazing- Alitherm 400 TBT :** 36mm TGU 36.8mm lam TGU^(Q)**If unglazed please tick above glass thickness for bead type.****Standard Thermal Rating:**Window Energy Rating A externally glazed and B internally glazed with 28mm
Clear, 1.2 Softcoat, Argon, Black W/edge (Q)**Product U value Special Requirements:** _____**Astragal bars for 28mm units only - please tick:** [] 25mm Flat bar

Hinge codes:

S=Standard Sobinco gear PAS24- Sobinco Safe gear

T/V Trickle vents require a minimum of 20mm add-on, fixed to the top of the window

Location	Design (viewed outside, please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add ons 20mm 30mm 42mm (Minimum of 20mm required with t/vents)			Special Requirements
						T/V					
			W		None	S		T			
					85	PAS24		B			
			H		150	2700		L			
					190 / 225	4000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700		L			
					190 / 225	4000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700		L			
					190 / 225	4000		R			

Location	Design (viewed outside , please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add ons 20mm 30mm 42mm (20, 30 or 42mm required with t/vents)			Special Requirements
						T/V					
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			
			W		None	S		T			
					85	PAS24		B			
			H		150	2700 4000		L			
					190 / 225	5000		R			