



HERITAGE 60 RESIDENTIAL/FRENCH DOOR ORDER/QUOTE FORM

Aluminium Direct Fax: 01453 827801

E-mail Orders: sop@atlas-aluminium.co.uk

Please tick for quote Page ____ of ____
 only ☐

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

Note: 28mm glazing only
 : Entrance doors can be coupled to 60mm fixed frames using a 20mm flush coupler
 : If a door is being coupled to a Heritage 47 window, please note this will be stepped where they are joined by a 25mm wide coupler
 : Internally beaded only
 : Standard outerframes can be face or concealed drainage, Open in is face drain only, low thresholds are face drain only

Please Circle Items Required

Please Circle/Tick Items Required

(Q) = Selection may need to be upgraded to meet Part Q

Part Q Compliant: Y / N

Colour: White (G) / Grey (7016M) / Black (9005M) /
 Dual Grey Ext (M) & White Int (G)

Handle Colour: White / Gold / Chrome / Black
 Satin Silver / Grey / Antique Black

Art Deco handle: Black / White / Brass / Satin Nickel

Hinge Colour: Grey / Black / White

Cylinder: STD 3* Security Key-Key / 3* Security Thumb Turn

Drainage: Face / Concealed

Fixed side frame profile width if applicable: 47mm / 60mm

Glass Supply: YES / Unglazed

Flat Panel Supply: YES / Unglazed

Tick which is required:

Door Set Energy Rating: B ☐ C ☐

(B only available on french doors)

U value 1.5 ☐ 1.6 ☐

Astragal Bar 25mm Flat bar ☐



(Please draw layout below)

With a handle block you must have solid
 transoms in the door sash.

Standard threshold ☐ Low threshold ☐

Trickle Vent: White / Black / Grey / Silver / Grey on White

Trickle vent widths 2700mm2=300mm, 4000mm2=400mm and 5000mm2=600mm



Note: Low ali thresholds are not weather rated and therefore not recommended for exposed locations.

Location	Design (viewed outside, please show T/vents, midrail dimensions, master door, astragal bars)	Qty In/Out	Sizes (mm) Including Cills & Add-ons		Cill	Thresh	Glass Spec (Tgh, Obs, Lead)	Addons 20mm 42mm (42mm required with t/vents)		Special Requirements
						T/V				
		Qty:	W		None	Std		T		
						Low Ali				
		In	H		150	2700				
						4000				
		Out	H		190 / 225	5000		L		
		In	H		150	2700				
						4000				
		Out	H		190 / 225	5000		R		
		In	H		150	2700				
						4000				
		Out	H		190 / 225	5000		R		
		In	H		150	2700				
						4000				

Location	Design (viewed outside , please show T/vents, midrail dimensions, master door, astragal bars)	Qty In/Out	Sizes (mm) Including Cills & Add-ons		Cill	Thresh	Glass Spec (Tgh, Obs, Lead)	Addons 20mm 42mm (42mm required with t/vents)		Special Requirements
						T/V				
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		
		Qty:	W		None 85	Std		T		
						Low Ali		B		
		In Out	H		150 190 / 225	2700 4000 5000		L		
								R		