

# Atlas Aluminium

Newton Centre, Brunel Way, Stroudwater Business  
Park, Stonehouse GL10 3SW

Reg address-Eden House, Reynolds Road, Beaconsfield, HP9 2FL



No: \_\_\_\_\_

Prod: \_\_\_\_\_

Del: \_\_\_\_\_

## VISO FOLD 1000 QUICKGLAZE BI-FOLD DOOR ORDER/QUOTE

Page \_\_\_\_ of \_\_\_\_.

Aluminium Direct Fax: 01453 827801

E-mail Orders: sop@atlas-aluminium.co.uk

Please tick for quote only ☐

Company Name (Acc No): \_\_\_\_\_

Signature: \_\_\_\_\_

Preferred Delivery Date: \_\_\_\_\_

Print Name: \_\_\_\_\_

Order Ref: \_\_\_\_\_

Date: \_\_\_\_\_ E-mail \_\_\_\_\_

confirmation: \_\_\_\_\_

### Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q

**System :** Slim sash quickglaze **Medium Sash:** quickglaze / wedge gasketed

**Outer frame:** STD DV14 (70mm frame) / DV17 (82mm frame)

**Part Q Compliant:** Y / N

**Colour:** White (G) / Grey (7016M) / Black (9005M) /  
Dual Grey Ext (M) & White Int (G)

**Master Door Handle:** Lever-Lever only

**Slave Door Handle** (if applicable): Lever-Lever / Intermediate

**Intermediate pop out Handles** (Slim sash only): Locking / Non-Locking

**Intermediate standard handles** (Medium sash only): Locking / Non-Locking

**Lever-Lever Handle Colour:** White / Black / Chrome

Grey / Satin Silver / Gold

**Intermediate Handle Colour:** White (recommended) / Black / Grey

**Hinge Colour:** White / Black (recommended)

**'D' Pull Handle** (on hinge): White / Black / Grey

**Magnetic Hold Open Catch:** None / White / Black / Grey / Chrome

**2200 EA Flush Sash Trickle Vent:** None / White / Black / Grey / Grey on white

**Number of Flush Sash Trickle vents:** \_\_\_\_\_ (Flush sash Trickle Vent EA 2200mm2)

**Trickle Vent:** None / White / Black / Grey / Silver / Grey on White

**Trickle Vent Equivalent area:** 2700 / 4000 / 5000 **Number TV's:** \_\_\_\_\_

Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm

**Glass Supply:** YES / Unglazed

**Glass Spec:** Double Glazing 28mm 28.8mm lam  
Triple Glazing 44mm 44.8mm lam

**If unglazed please tick glass thickness for gasket type.**

**Note:Triple glazing will require wedge gaskets.**

**Standard Thermal Rating:**

Door Energy Rating C with 28m Cl tgh, 1.2 Softcoat, Argon, Black W/edge (Q)

**Glass Special Requirements:** \_\_\_\_\_

**Product U value Special Requirements:** \_\_\_\_\_

**Threshold:** [ ] DV14 51.5mm rebated  
[ ] DV17 51.5mm (82mm deep)  
[ ] DV171 15mm low threshold open in  
[ ] DV271 15mm low threshold open out  
[ ] DV173 20mm low threshold open in and out  
[ ] DV176 integrated cill (175mm) open out only

**Note:** integrated cill requires DV17 outer frame (82mm deep frame- 30mm add-on not compatible)

**Delivery :** ASSEMBLED

FLAT PACK

**\*You will need to ensure able bodied people are available to assist with offloading at the delivery address. If this requirement is not met, you will be charged for the redelivery of the product.\***

**Note:** Low thresholds not weather rated and 3\* cylinders as standard

**Note:** Mullion dimensions can vary depending on style. External access is only available on bi-folds which have a 'lead' door.

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Qty	Cill	Sizes (mm) Including Cills & Add-ons		Addons 20mm 30mm 42mm (30 or 42mm required with t/vents)			Special Requirements
					W	H				
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Qty	Cill	Sizes (mm) Including Cills & Add-ons		Addons			Special Requirements
							20mm	30mm	42mm	
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W	(max 1200mm per sash)	T			
							B			
					H	(max 2500mm)	L			
							R			