

 roofs.sop@atlas-aluminium.co.uk Tel: 02838 327741 Fax: 02838 324358		SKYROOM FORM: QUOTE		ORDER		Please Tick		Customer Details:	
		Dimensions shown are all: Internal		External		Frame Width:			
		Roof Pitch:		Max Height restriction:					
		Remarks:							
Profile Colour								Customer Ref:	
External	Internal							Quote No:	
Alu White Caps	Standard White							Delivery Address:	
Stock Grey 7016m	Stock Grey 7016m								
Stock Black 9005m	Stock Black 9005m								
Non stock Ral	Non stock Ral								
External RAL: Finish								Tie Bars	
Internal RAL: Finish								Hidden Lazer (max 3 metres, design dependant)	
Double Glazed - 4/16/4 (24mm units)								Box Section (<i>max 4.7 metres</i>)	
Self clean Blue Solar/Low e								Roofvent	
Self clean Neutral Solar/Low e								Roofvent	
Self clean clear /Low e								Qty-	
Other:								Manual with pole	
								Electric opener	
Spacer Bar								Spindle colour	
Black Warm Edge								Wall Rocker switch operated	
Silver alu								Rain Sensor/Thermostat control (Analogue)	
Other:								Rain Sensor/Thermostat control (Digital)	
Internal Pelmet								Ridge Detail	
Internal Pelmet width from back of wall frame								Mark lil Ridge as standard	
Width :								Cresting Fleur de Lys	
								Fleur de Lys Finial	
								Ball Finial	
Ringbeam Specification								Downpipes	
Standard ringbeam								PVCU round downpipe (standard)	
Heavy Duty reinforced ringbeam								Aluminium round downpipe	
Note: Heavy duty ringbeam required over bi-folds or large patios.									
Maximum Heavy Duty beam span is 4 metres.									
		Print Name:		Signed:					
		Date:							