



Sliding Doors

Visoglide Plus Upgrade



Range	Visoglide Plus Upgrade
Finish	Polyester powder coating to BS6496 (Marine Grade +60 microns)
Appearance	Contemporary frame, sash and bead
Stock colours	White gloss, RAL 7016m, RAL 9005m and RAL 7016m on white
System glazing	Internally glazed
Thermal break	Polyamide thermally broken profile
Gaskets	Low line gasket for slimmer sightlines
Quickglaze	Standard Interlock
DER	down to B rating using suitable double glazed unit
U Value	down to 1.4 W/m ² k with double glazing and 1.1 W/m ² k with 36mm triple glazing
Locking system	Shootbolt operated
Security	PAS24 upgraded specification available
Cylinder	Standard Mila, upgrade to Ultion for PAS24
Rollers	Tested to 50,000 cycles (approx 25 years use)
Handles	Key locking handles by Smart
Frame Depth	Two track 104.5mm / three track 171.5mm
Interlock sightline	Standard 83mm and Slimline 35mm
Max o/a height per sash	2700mm
Max Sash weight	200kg
Max o/a width per sash	Within above limitations
Glazing sizes	28mm double glazing and 36mm triple glazing
Air Test	Class 3 600Pa
Water test	Class 7A 300Pa
Wind test	Class AE 2400Pa
Add ons	42mm add on available
Threshold	Threshold with internal upstand available (flush internal floor levels)
Trickle Vents	Trickle vents are fitted into a 42mm add on

Service	
Delivery	On dedicated Atlas vehicles (outer frame flat pack kit available)